

## Belimo Actuators

### Actuator Specification

### Maximum Damper Size

Style	VA rating	Motor time	Spring return	Switch	Torque	OBS	PBS	OBN	PBN
LF 120	7.5	<40-75	<25		35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
LF 120-S	7.5	<40-75	<25	*	35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
LF 24	7	<40-75	<25		35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
LF 24-S	7	<40-75	<25	*	35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
NF 120	7	<75	<60		60in-lb	12 SF	8.6 SF	20 SF	15 SF
NF 120-S	7	<75	<60	*	60in-lb	12 SF	8.6 SF	20 SF	15 SF
NF 24	8	<75	<60		60in-lb	12 SF	8.6 SF	20 SF	15 SF
NF 24-S	8	<75	<60	*	60in-lb	12 SF	8.6 SF	20 SF	15 SF
AF 120	10	150	<20		133in-lb	26.5 SF	19 SF	44 SF	33 SF
AF 120-S	10	150	<20	*	133in-lb	26.5 SF	19 SF	44 SF	33 SF
AF 24	10	150	<20		133in-lb	26.5 SF	19 SF	44 SF	33 SF
AF 24-S	10	150	<20	*	133in-lb	26.5 SF	19 SF	44 SF	33 SF

### Modulating Actuators

LF24-SR	5	150	<25		35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
LF24-SR-S	5	150	<25	*	35in-lb	7 SF	5 SF	11.5 SF	8.6 SF
NF24-SR	6	150	<60		60in-lb	12 SF	8.6 SF	20 SF	15 SF
NF24-SR-S	6	150	<60	*	60in-lb	12 SF	8.6 SF	20 SF	15 SF
AF24-SR	10	150	<20		133in-lb	26.5 SF	19 SF	44 SF	33 SF



**Standard Metal Products Mfg. LLC**

DAMPERS & LOUVERS FOR THE HVAC INDUSTRY  
 P.O. Box 32610 8030 Ranchers Road NE Minneapolis, MN 55432 763.783.7173 (P) 763.785.6977 (F) 1.800.297.9360